



**Specifications Sylvania LED Downlight**  
**Start 5in1 50-125 White 12W 1150lm**  
**114D - 827-830-840 CCT| IP20**



[View Product](#)

## General Information

|                          |                              |
|--------------------------|------------------------------|
| SKU                      | 255267                       |
| EAN                      | 5410288531489                |
| Brand                    | Sylvania                     |
| Manufacturer Name        | ST DLIGHT 5IN1 50-125 1150LM |
| Any Lamp all-in warranty | 3 Years                      |
| Average Lifetime (h)     | 55000                        |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 1x18              |
| Wattage                     | 12                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 865 Daylight      |
| Colour temperature (Kelvin) | 6500 Daylight     |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |                                    |
|--------------------------|------------------------------------|
| Beam Angle (degree)      | 114                                |
| Luminous Flux (Lumen)    | 1150                               |
| Luminous Efficacy (lm/W) | 95.8                               |
| Power factor             | >0.70                              |
| Unified Glare Rating     | < 25 - for hallways and staircases |
| Optical Cover            | Opal                               |
| Product Type Category    | LED Downlight                      |

### Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| IP-rating              | IP20                   |
| Impact Protection (IK) | IK05 - 0.70 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Plastic                |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

### Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 22  |
| Diameter (mm) | 165 |

### Sensor Information

|                |                                   |
|----------------|-----------------------------------|
| Type of sensor | <b>Why Any-lamp?</b><br>No Sensor |
|----------------|-----------------------------------|

💡 Order from the **largest lighting specialist** in Europe 📄 **Customised** quotation

🏆 Up to **7 years warranty** ↩️ **Easy** return process