



Specifications Multipack 4x Philips  
LED Downlight Ledinaire DN065B  
Metal White 19W 2000lm 110D -  
830-840-865 CCT | 225mm - Cutout  
200mm - IP20

[View Product](#)

## General Information

|                          |                                                      |
|--------------------------|------------------------------------------------------|
| SKU                      | 253041                                               |
| EAN                      | 8719157059374                                        |
| Brand                    | Philips                                              |
| Manufacturer Name        | Multipack 4x DN065B G4 LED20/830_840_865 19W D200 RD |
| Any Lamp all-in warranty | 3 Years                                              |
| Average Lifetime (h)     | 30000                                                |

## Technical Information

|                             |                                                 |
|-----------------------------|-------------------------------------------------|
| Emergency Lighting          | No Emergency Unit                               |
| Tiltable                    | No                                              |
| Technology                  | LED Integrated                                  |
| Wattage                     | 19                                              |
| Voltage (V)                 | 220-240                                         |
| Dimmable                    | Not Dimmable                                    |
| Colour Code                 | 830 Warm White, 840 Cool White, 865 Daylight    |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White, 6500 Daylight |
| Colour Rendering (Ra)       | 80-89                                           |
| Colour of Light             | White                                           |
| Light colour options        | CCT                                             |
| Including bulb              | Yes                                             |

|                          |                                       |
|--------------------------|---------------------------------------|
| Amount of bulbs required | 1                                     |
| Beam Angle (degree)      | 110                                   |
| Luminous Flux (Lumen)    | 2000                                  |
| Luminous Efficacy (lm/W) | 105                                   |
| Power factor             | >0.90                                 |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | Plastic                               |
| Finish of Reflector      | Frosted                               |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 200                    |
| IP-rating              | IP20                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Metal                  |
| Colour of the Fixture  | White                  |
| Fixture Connection     | Screw terminal, 2-pole |
| Series                 | DN065B                 |

## Dimensions

Diameter (mm)

**Why Any-lamp?**

225

## Sensor Information

Order from the **largest lighting specialist** in Europe



**Customised** quotation

Type of sensor



**Up to 7 years warranty**

No Sensor



**Easy** return process

